









Commissioning of a KLOVER pellet stove



Once your KLOVER pellet stove has been installed, commissioning is an essential step in configuring your furnace and understanding its operation. This should preferably be carried out by a certified technician.

Steps to follow

1. Fill the pellet tank. You can fill it up to a maximum of 2cm below the loading hatch seal.
2. Check that the loading hatch and firebox door are closed.
3. Plug the electrical socket into the stove. Generally speaking, the connection is located at the back of the stove. For flat models, it is located on the front of the stove at the bottom. Plug it in correctly.
4. Switch on the stove by turning the I/O button to position I. This button is located next to the stove's electrical socket. The LEDs on the control panel will light up if the plug has been properly connected.
5. Add 3 batteries (AAA) to the remote control.
6. Set the remote control to the desired language (FRE for French) using the buttons  .
7. A Before installation message will appear. Press NO.
8. Continue to press the Set button until the main menu is displayed. If the message Device not found appears, we refer you to our article Device not found.
9. Press the Set button to go to the stove settings. Then go to the Stand-By menu, which you can activate with   A  should appear. If you do not activate Stand-By, the remote control thermostat will not be activated.
10. Go to the stove settings menu by pressing the Set button. Then go to the Initial load menu. A message PAR CHARGER IN OFF PREMI UP will appear. Press  so that the auger can turn. This is an important point, as this is the first ignition, so you'll only have to do it once. If you skip this step, the furnace may fail to ignite, as there are not enough pellets in the inferno. Loading takes about 1 minute and 30 seconds.
11. Go to the stove settings menu by pressing the Set button. Then go to the Set Clock menu. Set the stove's time and date at  .
12. Finally, switch on the pellet stove using the remote control by pressing the   Wait about 10-15 minutes for a flame to appear.

When the stove is first lit, it may smell of paint and emit a mist. Don't panic, this is just paint settling on the stove as it is new. This phenomenon occurs during the first and second start-ups.

Ventilate the room well during this period. Let the pellet stove run for about 1 hour at full power (flame power 5 and fan power 1-2). Once this is done, you can use your pellet stove as normal.

Commissioning of a KLOVER pellet stove