DECLARATION OF PERFORMANCE (DOP)

| | NO. 90065601-CPR-20150529 | |
|----|---|--|
| 1. | Product Type: | Freestanding stove Scan 65 |
| 2. | Type, batch or serial number: | Scan 65 series (Scan 65-2, Scan 65-4, Scan 65-6, Scan 65-8, Scan 65-10) |
| З. | Intended use of the product: | Heat distribution/room heating Without hot water supply Fuel type: Wood |
| 4. | Name and Address of the manufacturer: | Scan A/S Glasvænget 3-9 5492 Vissenbjerg |
| 5. | Contact address: | No relevance |
| 6. | AVCP System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V | System 3 |
| 7. | Notified body: Test report no: | RWE Power AG NB-No 1427 FSPS-Wa 2308 EN |
| 8. | Declared performance | |
| | Harmonized technical specification | EN 13240:2001/A2:2004/AC:2007 |
| | Essential characteristics | Performance |
| | Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out | A1 Minimum distances in mm: Rear: 150 Sides: 500 Front: 1000 NPD |
| | Emission of combustion products | CO [1221 mg/Nm ³] NOx [117 mg/Nm ³] OGC [92 mg/Nm ³] Dust [<20 mg/Nm ³] |
| | Surface temperature | Pass |
| | Electrical safety | - |
| | Cleanability | Pass |
| | Maximum water operating pressure | - |
| | Flue gas temperature at nominal heat output [EN] | T [264°C] |
| | Mechanical resistance (to carry a chimney/flue) | NPD |
| | Thermal outputNormal heat outputRoom heating outputWater heating output | 6 kW |
| | Energy efficiency | ŋ [79 %] |

DECLARATION:

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Morten Bach (R&D LAB)

Vissenbjerg, 27.08.2015

(Place and date of issue)

SC

Monto Bal

(Signatute)